



Contraction of the second seco	ltem no. 93155-25	Self-tapping screw 5.5 x 20-25, sealing washer Ø 16 mm Drilling capacity steel 0.5 mm - 2.0 mm Drilling capacity aluminum 0.5 mm - 2.0 mm Packaging unit (PU) 100 pieces
	93160-25	Self-tapping screw 6.0 x 25-25, sealing washer Ø 16 mm Drilling capacity steel 0.4 mm - 2.0 mm Drilling capacity aluminum 0.5 mm - 2.0 mm Packaging unit (PU) 100 pieces
	93161-25	PREMIUM Self-tapping screw 6.0 x 25, sealing washer Ø 16 mm Drilling capacity steel0.5 mm - 1.5 mm Drilling capacity aluminum0.4 mm - 2.0 mm Packaging unit (PU)100 pieces
	93155-26 Beware of metal swarf on the roof!	Self-drilling screw 5.5 x 25, sealing washer Ø 16 mm Drilling capacity steel 0.4 mm - 1.5 mm Drilling capacity aluminum 0.4 mm - 5.0 mm Packaging unit (PU) 100 pieces
The second second	93148-20	Self-drilling screw 4.8 x 20 for Internal Connector RAIL Drilling capacity steel 0.5 mm - 3.0 mm Drilling capacity aluminum 0.7 mm - 4.0 mm Packaging unit (PU) 100 pieces





Technical Data

Material Stainless steel, EPDM rubber seals

- Design Tool SL-Rack-Configurator Solar.Pro.Tool.
- StatikThe structural analysis is carried out in accordance with the current country-specific standards (EN 1991, EC1 for
Germany). Depending on snow loads, wind loads, or when utilizing large modules, it may be necessary to use more
than the usual 4 fastening points. Make sure to observe the installation manual of the respective module manufac-
turer. The load-bearing capacity of the roof has not been evaluated by SL Rack.



is important to us!

It is our top priority to make the installation process for you as quick, easy and efficient as possible. Please share your experiences, ideas or criticism with us, so we can continue to improve our products and develop new ones.



SL Rack Feedback
Provide Feedback >



SL Rack Website Check it out >



SL Rack YouTube Watch videos >



Subject to technical changes and misprints. Version 01/2023 V3